

10-30-00

A

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: FISHER ET AL.  
 Docket: 8964.72USU1  
 Title: PORTABLE APPARATUS FOR IDENTIFICATION VERIFICATION

CERTIFICATE UNDER 37 CFR 1.10

'Express Mail' mailing label number: EL649973745US

Date of Deposit: October 27, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service 'Express Mail Post Office To Addressee' service under 37 CFR 1.10 and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231

By:

Name: Chatia Lambert

BOX PATENT APPLICATION  
 Assistant Commissioner for Patents  
 Washington, D.C. 20231

Sir:

We are transmitting herewith the attached:

- ☒ Transmittal sheet, in duplicate, containing Certificate under 37 CFR 1.10.
- ☒ Utility Patent Application: Spec. 16 pgs; 27 claims; Abstract 1 pg.  
The fee has been calculated as shown below in the 'Claims as Filed' table.
- ☒ 5 sheets of drawings
- ☒ An unsigned Combined Declaration and Power of Attorney
- ☒ A check in the amount of \$836.00 to cover the Filing Fee
- ☒ Return postcard

**CLAIMS AS FILED**

Number of Claims Filed	In Excess of:	Number Extra	Rate	Fee
<b>Basic Filing Fee</b>				\$710.00
<b>Total Claims</b>				
27	20	7	x 18.00	\$126.00
<b>Independent Claims</b>				
2	3	0	x 80.00	\$0.00
<b>MULTIPLE DEPENDENT CLAIM FEE</b>				\$0.00
<b>TOTAL FILING FEE</b>				<b>\$836.00</b>

Please charge any additional fees or credit overpayment to Deposit Account No. 13-2725. A duplicate of this sheet is enclosed.

**MERCHANT & GOULD P.C.**  
 P.O. Box 2903, Minneapolis, MN 55402-0903  
 (612) 332-5300

By:

Name: Alan G. Gorman

Reg. No.: 38,472

Initials: AGG:PSTtdm



**23552**

PATENT TRADEMARK OFFICE

(PTO TRANSMITTAL - NEW FILING)

# PORTABLE APPARATUS FOR IDENTIFICATION VERIFICATION

## Related Applications

This application claims the benefit of provisional application,  
U.S. Serial No. 60/162,592, filed on October 29, 1999, entitled "PORTABLE  
5 APPARATUS FOR IDENTIFICATION VERIFICATION", by Fisher et al.

## Technical Field

The present invention relates to apparatus for the live scanning of fingerprint,  
facial and crime scene images and more particularly to a portable apparatus for the  
10 scanning and capture of fingerprint, facial and crime scene images and the wireless  
transmission of said images to a central location for identity verification.

## Background of the Invention

Over the years, the most commonly used techniques for both identity  
15 verification and the identification of potential crime suspects have been the use of  
fingerprints and photographs or "mug shots".

Originally, fingerprinting was done by inking a suspect's finger and  
applying the inked finger to paper. As can be readily understood, fingerprint  
information in this form was difficult to use. Making a fingerprint match was an  
20 extremely time-consuming task. Digital technology significantly advanced the art of  
fingerprinting. Inked images could be scanned, the image digitized and recorded in a  
manner that could later be searched in a reasonably expeditious manner by  
computer. Problems arose, however, due to the quality of inked images. Over- and  
under-inking resulted in blurred or vague images, thus rendering the digitized  
25 information useless. Further, the process of scanning an inked image was relatively  
time-consuming.

These and other problems led to "live scanning". According to live  
scanning techniques, the fingerprint of a suspect is scanned directly from the  
suspect's finger, as opposed to being scanned from an inked image of the print. More  
30 specifically, live scans are those procedures that capture fingerprint ridge detail in a  
manner which allows for the immediate processing of the fingerprint image with a  
computer. Original work in the field dates back to original patents filed in 1964

concerning techniques used to capture high contrast images of fingerprints for photographic or digital captures of fingerprints.

Since their introduction, live scans have become an important tool for law enforcement. The live scan has the potential to overcome inherent weaknesses in the ink capture of fingerprints and provide immediate transmission of fingerprint images; and allow for image enhancement if necessary.

These characteristics provide law enforcement with the ability to improve the quality of the fingerprint database, thereby improving the likelihood that identifications may be made either from latent fingerprints or from identity verification checks. In addition, live scan fingerprints are easily adaptable to computerized storage and processing techniques, increasing cooperation and fingerprint data transfer between various police agencies.

Systems, which optically, or optically and mechanically, generate fingerprint images have been in use for quite some time. Several such fingerprinting systems are disclosed in Fishbine et al., U.S. Pat. Nos. 4,811,414 and 4,933,976; Ruell German Patent No. 3423886 A1; Becker U.S. Pat. No. 3,482,498; McMahon U.S. Pat. No. 3,975,711; Schiller U.S. Pat. Nos. 4,544,267 and 4,322,163; Marcus U.S. Pat. No. 4,533,837 and White U.S. Pat. No. 3,200,704. However, the problem with all of these systems is that they are only capable of providing optical or optical and mechanical fingerprint images at a central location such as the police station.

U.S. Patent No. 5,222,152 to Fishbine et. al. solved this problem by providing a portable and lightweight fingerprint scanning system which can optically generate fingerprint images. This system is ideal for traffic officers and other law enforcement professionals who want to perform immediate identity and background checks on individuals while in the field. The system described in Fishbine et al, Patent No. 5,222,152, is uses the optical principle of total internal reflection. When a finger is positioned on a finger-receiving surface, an optical image of the ridge and valley pattern on the surface of the finger (i.e., the fingerprint) is propagated from the finger-receiving surface.

The finger-receiving surface is a prism with illumination provided on side surfaces by an illumination source that consists of light-emitting diodes attached to the side surfaces of the prism. The bottom surface of the prism is coated with an

opaque material such as black paint. The prism is designed to utilize the optical principle of frustration of total internal reflection as described in Fishbine et al. U.S. Pat. No. 4,811,414. These properties result in a visual fingerprint image of a finger placed on the finger-receiving surface with "light" areas corresponding to ridges of the fingerprint and "dark" areas corresponding to valleys of the fingerprint. The image is captured using a video camera and the data is digitized for display, storage, and transmission. Optical fingerprint sensors, as described in the reference patent, require complex optical path corrections. Video cameras, prisms, lenses, and mirrors used in the system must be precisely located.

10                   An investigator at an incident scene is often at risk due to lack of information. If a suspect or witness feels the investigator will obtain information that will incriminate them, the risk to the investigator is increased. In these situations, investigator safety is increased if the portable device for capturing images may be operated using a single hand. Although mobile, the system described in  
15   Fishbine et al, Patent No. 5,222,152, does not allow for single-handed operation. Single handed operation means the ability to hold the device in one hand and use the same hand to control the device while conducting an investigation. The portable system described in Fishbine et al, Patent No. 5,222,152, required the officer to use both hands, holding the device in one hand while using the other hand to capture  
20   images or enter text. In capturing images, the operator holds the device in one hand and is required to align the suspect's finger in the correct position to capture a usable print. There is a need for a system that allows for single hand operation and image gathering. This would provide a law enforcement officer with additional safety by having one hand free to protect oneself from potential harm that may be inflicted by  
25   a suspect.

                  The orientation and location of a captured fingerprint significantly impacts the quality of the response received from the search system. It is important to align the finger along the capture surface properly, capture the core of the print, and prevent movement by the witness or suspect as the print is being captured. It is  
30   desirable for the system to orient and align the finger without requiring the officer to use both hands.

Any optical fingerprint system is susceptible to intense ambient lighting. Intense ambient light which strikes the fingerprint receiving surface produces bright images on the video camera which captures the fingerprint image. If the ambient light intensity is equivalent to the light source of the fingerprint capture system, the bright spots will interfere with the fingerprint image being captured. Thus, when the finger-receiving surface on the system disclosed in Fishbine et al, Patent No. 5,222,152, was exposed directly to ambient lighting, the operator was required to reorient the device to eliminate interference from the bright ambient lighting. During an investigation, these extra actions are undesirable.

#### Summary of the Invention

In accordance with the present invention, the above and other problems are solved by providing the present invention which is a portable and lightweight fingerprint scanning apparatus that can optically scan and record fingerprint images in the field and transmit said images to a wireless mobile unit for processing and subsequent wireless transmission to a central location for the purpose of providing immediate identity and background checks on individuals being fingerprinted in the field. The apparatus of the present invention includes a fingerprint scanner and a wireless transmitter to transmit the fingerprint image to a mobile unit. In the preferred embodiment the present invention also provides for the capability of using a video camera to capture a photographic image or "mug shot" for wireless transmission to a mobile unit. An embodiment of the present invention also provides the ability to preview the fingerprint and "mug shot" images on a video monitor and to control transmission and processing of the fingerprint and "mug shot" images by the mobile unit using a terminal processor or keypad located on the portable fingerprint scanning apparatus. In the present embodiment, the terminal processor within the portable device may be a Pentium processor. The present invention allows law enforcement professionals to perform immediate identity and background checks on an individual while in the field.

The utility of the present invention is that it may be operated singled handedly, and, it eliminates the problems caused by direct exposure of the finger-receiving surface to bright ambient lighting. This portable apparatus may also use solid state fingerprint sensors that eliminate the need for precise locations of

components, thus increasing reliability of the sensor over the life of the apparatus. Solid state sensors are also less sensitive to wet or dry fingerprints. The system also provides a mechanical means of providing both finger alignment and core position location thereby reducing the workload of the investigator while capturing a fingerprint. This reduction in workload improves investigator safety by allowing closer monitoring of the person being fingerprinted. The system also provides for the capture of "latent fingerprints" at the scene of a crime. The ability to search and capture "latent fingerprints" with a portable device reduces investigation time.

These and various other features as well as advantages, which characterize the present invention, will be apparent from a reading of the following detailed description and a review of the associated drawings.

#### Brief Description of the Drawings

Fig. 1 illustrates a hardware component block diagram of the portable identification verification system;

Fig. 2A - 2B illustrates perspective views of the present portable device, showing a light baffle attached and removed;

Fig. 3 illustrates perspective views of the present portable device, showing the ergonomic design of the single hand operation handle;

Fig. 4 illustrates a side view of the present portable device, showing the magnetic stripe and smart card reader and removably attached latent print alignment guide;

Fig. 5 is a flow diagram illustrating a flow diagram for a rolled fingerprint capture; and

Fig. 6 is a communication flow diagram illustrating the communication of information between the portable device and various system to which the portable device connects; and

Fig. 7 is an exemplary hardware environment for one embodiment of the present invention.



geographical position also allows the investigator to use advanced mapping programs that identify surrounding areas, giving the investigator additional information about the incident site. The same mapping function would also allow coordination and direction between different investigative teams or personnel. The automated detection of geographical position may be obtained using the global positioning system (GPS).

Investigators often are required to work in an area which potentially contains risk to the investigator. Suspects or witnesses are more likely to use physical violence if they feel the investigator has access to information that could incriminate them. It is desirable for the investigator to be able to send a message requesting assistance by using a single button; transmitting an “officer needs assistance” message to the central site. The expeditious use of this function could be the difference between life and death for an investigator in a violent situation.

Wireless transmittal of data to a central site provides expedient flow of information. The prior invention transmits data a short distance to a mobile unit that in turn relayed the information to the central site via existing law enforcement networks. The ability to directly link information to a central site, eliminating the need for a mobile unit as intermediary, gives the investigator increased flexibility, reliability and reduces transmission delays.

## Detailed Description of the Invention

In the following detailed description of the preferred embodiments reference is made to the accompanying drawings that form a part hereof, and is shown by way of illustration specific embodiments in which the invention may be practiced. It is to be understood that the other embodiments may be utilized and structural changes may be made without departing from the scope of the present invention.

Fig. 1 illustrates a hardware component block diagram of the portable identification verification system in accordance with the present invention. The major components of the portable identification verification system include image capture devices 26, external data entry devices 27, external interfaces 28, and a terminal 3. The terminal 3 controls the various functions of the portable



The embodiment of the system shown in Figs. 2A and 2B illustrates the incorporation of a removable light baffle that prevents excessive ambient light from interfering with the fingerprint scan. Fig. 2A illustrates a light baffle 30 removed from the fingerprint receiving surface 11 and Fig. 2B shows when the baffle 30 is mounted on the apparatus 12. The baffle mounting mechanism also aligns the fingerprint within the finger-receiving surface such that the fingerprint characteristics of interest are properly located with respect to the fingerprint capture sensor 1. The finger to be printed is inserted into the baffle 30 and slid forward against the baffle mounting mechanism. The front end of the finger is thus located such that the core of the fingerprint is within the central region of the fingerprint-receiving surface 11. The sides of the baffle mounting mechanism provide a channel that aligns the finger with the fingerprint-receiving surface 11 and minimizes the ability to rotate the finger during the fingerprint capture. The baffle 30 itself is removable for operation when ambient lighting does not require the baffle or when alignment and rotation mechanisms are not required, e.g., during roll fingerprint captures.

During the capture of a fingerprint it is desirable to position the core of the fingerprint over the center portion of the fingerprint-receiving surface 11. The core is the portion of the fingerprint that contains the most information, or minutiae used by automated fingerprint identification systems (AFIS). It also improves AFIS performance if the fingerprint is aligned with the fingerprint-receiving surface 11 such that the fingerprint image is not rotated when captured. An apparatus such as a light baffle 30, that provides both finger alignment and core position location will reduce the workload of the investigator while capturing a fingerprint. This reduction

in workload improves investigator safety by allowing closer monitoring of the person being fingerprinted.

The requirement to capture good quality images will be initiated by the physical finger guides and finger positional aids. After an image is captured, the images are processed by image quality control (IQC) algorithms to judge the quality of the image in regards to whether the image is light, dark, or too small. These algorithms may be applied to both rolled and flat fingerprint images.

The image quality algorithms process finger print images as follows. Assume an image of width  $W_T$  by height  $H_T$  pixels is captured by the fingerprint capture sensor 1. The image is broken down into smaller rectangular regions ( $R_1..R_N$ ) of width  $W_R$  by height  $H_R$  pixels. The size of these smaller rectangles is tuned to the particular image capture device. The region size is chosen to fit uniformly within the captured image. The captured image may then be treated as a number of rectangles  $R_N$ . For each region  $R_1..R_N$ , the pixels in the rectangle are then analyzed. The value of each pixel is compared to a dark and light threshold value  $P_{dark}$  and  $P_{light}$ . These dark and light threshold values are tuned to the particular image capture device. A count is kept of the number of dark and light pixels within each region. Each region  $R_1..R_N$  is then counted as dark, light, or both by comparing the number of dark or light pixels against another set of threshold values  $P_{darkcnt}$  and  $P_{lightcnt}$ . These dark and light threshold values are also tuned to the particular image capture device. A count is kept of the number of dark and light regions within the total number of regions.

The image is then evaluated as dark, light, or both by comparing the number of dark or light regions against a threshold value  $P_{darkpct}$  and  $P_{lightpct}$ . These numbers are expressed as percentages of dark or light regions as compared to the total number of regions. These dark and light threshold values are also tuned to the particular image capture device. The extent of each row and column of regions that is not light is determined. Based upon the largest and smallest region extent in both the horizontal and vertical directions, the size of the image is determined. The extent of the image height and width are compared to threshold values  $H_l$  and  $W_l$  to determine if the image is small. These threshold values are tuned to the particular

image capture device. Using the light, dark, and small determinations, a message is presented to the user that the image is acceptable or should be retaken.

The present embodiment of the system also incorporates processing algorithms that allow the capture of a roll fingerprint (as described in Fig. 5).

5 Incorporating the ability to “roll” the fingerprint as done in central site live scan systems may enhance the fingerprint image described in the referenced disclosure. In capturing a roll fingerprint the left edge of the finger is placed on the left end of the fingerprint-receiving surface 11. The finger is then rolled from left to right on the receiving surface 11. The image recording device tracks the finger image as it rolls  
10 across the receiving surface 11 and records only a concatenated image of the fingerprint in contact with the receiving surface 11. Since more area of the fingerprint is recorded, the roll fingerprint provides increased data for comparison by automated fingerprint identification systems to fingerprint databases.

Fig. 3 illustrates a perspective view of the present portable device  
15 showing the present invention ergonomic design of the handle for single hand operation. The current embodiment implements a packaging approach with an ergonomic grip that allows the user to hold the device with either hand. The grip is tapered and formed to allow the user a comfortable hold on the grip while the thumb and forefinger are free to operate the controls of the apparatus. The controls are  
20 implemented such that the user may operate switches on a keypad, using the thumb or forefinger of either hand, to step through the functionality of the device. Fig. 3 illustrates the current physical embodiment of the portable device, showing an embodiment of the ergonomic grip 15 and a keypad 4. The keypad 4 is located with three primary switches 24 centered within easy reach of the operator’s thumb. The  
25 user is able to control software functionality using menus shown on the display 13 and the three primary switches. The fourth switch 25, which in the present embodiment is an ASSIST switch, is protected by a bezel and located farthest from the center of the grip 15 to prevent inadvertent operation.

The current embodiment of the apparatus also includes an “Assistance”  
30 function that generates an emergency message that is transmitted to the central site. The investigator presses a dedicated button, the ASSIST switch 25, that is interpreted by the software. The investigator is asked to confirm the transmission by

pressing "yes" and the message is then sent to the central site via the wireless transmission method employed. The assistance request will be done silently without indicating to other parties of the activation. The interpretation and distribution of the request may be customized to the operating environment of the hand-held unit.

5                    Fig. 4 illustrates a side view of the present portable device, showing the magnetic stripe and smart card reader and removably attached latent print alignment guide according to the present invention. The photo capture sensor 2 for capture of facial and incident scene images included in the current embodiment of the apparatus includes high magnification optics. When combined with a removable  
10    apparatus 17 the photo capture sensor may be used to obtain latent fingerprint images that approach law enforcement fingerprint image quality specifications. The removable apparatus will provide a mechanism for limiting ambient light from hitting the latent fingerprint and will provide a variable illumination source with level controls. The lighting source in the current embodiment is made up of CCFL  
15    fluorescent lights with opal glass diffusers. Future embodiments could include, but are not limited to, LED, ultraviolet, or incandescent light sources. In addition to lighting control, the removable apparatus may provide external optics 16 for optical corrections to the fingerprint image. The alignment opening 18 on the front of the removable attached apparatus is placed over the latent fingerprint and the latent  
20    search option is commanded from the user interface. The terminal then sets the optical magnification of the photo capture sensor to scale the spacing of the fingerprint image pixels to 500 dots per inch. The lighting level is adjusted to optimize the fingerprint image. This image is then captured for display, recording, or wireless transmittal to the central site. The apparatus includes the ability to  
25    isolate the fingerprint within the captured image and enhance the fingerprint image prior to transmittal or recording. Enhancements include, but are not limited to, thresholding, automated contrast enhancement, sharpness enhancement, or image inversion. This image is then used to conduct short duration searches on an automated fingerprint identification system using the incident scene latent  
30    fingerprint(s).

The photo capture sensor 2 in the current invention has the ability to capture photo images even in complete darkness. The sensor incorporates infrared

LEDs as an illumination source. The photo capture sensor is capable of capturing black and white photo images using this illumination. In the current embodiment the device uses a video camera, such as a Sony video camera -model number FCB-EX470L, with integrated infrared LEDs. An alternate configuration could include a  
5 single board camera such as the Edmund Scientific high resolution monochrome micro camera, model number J53-307, along with standalone infrared LEDs and external lens magnification for latent capture.

Incident scenes are not always well lit. Traditional cameras using a flash system provide only a momentary improvement in lighting. They do not allow  
10 the operator to view the incident scene under the same lighting that the image will be captured. The ability to operate under an infrared source and display live video allows the operator to preview the images about to be recorded. The infrared source also overcomes lighting limitations and improves image quality. In the extreme condition that no light is available at the incident scene the combination of infrared  
15 light source and live video display gives the investigator a limited night sight capability.

The current embodiment of the system incorporates audio capture 8 via a far field microphone and digital audio chip set which will enable digital recording, voice recognition applications and speech recognition. The current  
20 embodiment of the system incorporates a sound card such as a SoundBlaster® compatible PC104 circuit card or an ADTECH PC104-3210. Future embodiments may incorporate SoundBlaster compatible chipsets, such as the Analog Devices AD1816 or Aureal Vortex 2. From the teachings provided herein, those skilled in the art appreciate that the foregoing description sets forth one embodiment of a  
25 soundcard, although other object circuit cards are possible.

Digital recordings may also be captured, stored, and transmitted to central sites to enable complete descriptions and demographic information to be filed along with incident reports. Digital recordings of incident scene witnesses or suspects may be retained for later analysis and identification purposes. Speech  
30 recognition will enable voice-activated control of the apparatus. The audio range of the device may be from about 200 to 3700 Hz. Sampling may be accomplished at

approximately 7400 Hz or greater to insure sufficient frequency resolution for post processing algorithms at central sites.

The system further includes a text entry device. In the current embodiment, the text entry device includes a keypad 4 and rotary dial. In addition, the system includes a magnetic card reader 5 that is attached to a dedicated RS-232 interface that allows the investigator to scan data directly from drivers' licenses, credit cards, or other forms of cards using magnetic stripes into the apparatus. An alternative embodiment could implement a bar code reader 6 in place of the magnetic card reader. In an alternative embodiment of the apparatus, a combined magnetic stripe and smart card reader 7 may be implemented in place of the magnetic stripe reader. The data from the magnetic stripe, smart card, or bar code reader may then be captured, stored, and transmitted wirelessly along with other information from the incident. The magnetic card reader 4, bar code reader 6, and smart card reader 7, are commercially available.

As illustrated in Figures 2 and 4, the apparatus includes both a docking connector 23 for direct link to a mobile unit in a squad car and a wireless connectivity device (see Fig. 1) via an RF link from the apparatus to the mobile unit in a squad car as shown in Fig. 6. This RF link may be a 2.4 GHz spread spectrum receiver/transmitter that provides a serial data stream to the mobile unit. The communication link may be a serial port, such as an RS-232 serial port, on the mobile unit in the squad car. In a preferred embodiment of the apparatus a data link from the apparatus to the mobile unit in the car may use a PCM/CIA port on the mobile unit to provide a 2.4 GHz spread spectrum signal capable of over 2.0 megabits/second communication. An alternative configuration providing lower cost may transmit data via a 900 Mhz signal with data rates from about 19.2 kilobits/second to 115 kilobits/second. Both 2.4 GHz and 900 MHz are considered free frequency bands where general purpose communication may be accomplished. The specification of these frequencies provides for lower cost of hardware. However, embodiments of the apparatus could include other frequencies and data rates as specified by the operating agency.

Fig. 5 is a flow diagram illustrating a flow diagram for a rolled fingerprint capture according to the present invention. A rolled fingerprint image is



which the portable device connects according to the present invention. Another alternative configuration would eliminate all links to the mobile unit by providing a wireless link 22 from the apparatus 35 directly to the central site 36 via a communication switch 37 as shown in Fig. 6. The wireless format could be cellular (Cellular Digital Packet Data (CDPD), Mobitex, PCS, or other cellular service) or an RF network currently available in an area where the apparatus will be used. The types of coverage would be obtained by contacting local wireless service providers. The direct wireless link 22 is implemented via a PCM/CIA card such as the Novatel Merlin wireless modem.

The current embodiment of the apparatus includes interfaces to incorporate Global Positioning System, or GPS, satellite access 20 (as shown in Fig. 6) in the device. The current GPS interface may be accomplished via a dedicated RS-232 serial channel that communicates with available commercial GPS location sensors, such as the Global American GE7986 GPC receiver, in a PC104 form factor. Alternative configurations could interface with commercial GPS sensors using PCM/CIA interfaces such as the Premier Electronics Marco Polo GPS system. Future embodiments may directly incorporate GPS chipsets, such as the Rockwell 5-Channel GPS receiver. The GPS system may provide the user geographical location information within 25 meters. Advanced embodiments of the apparatus may provide geographical location information within 25 centimeters using differential GPS. The information provided by the GPS is available to other applications on the apparatus that provide functions for mapping or giving directions to investigators or other personnel involved in an incident.

Referring to Fig. 7, another hardware environment for identification and verification is shown 700 according to the present invention. The present invention may be implemented using an identification and verification processor 730, comprised of a processor 710 and memory (RAM) 740. It is envisioned that attached to the identification and verification processor 730 may be a memory device 740. Also included in this embodiment may be input devices 750, sensors to detect and input the desired image / data and interface to the user for downloading data and commands.



The identification and verification processor 730 may operate under the control of an operating system. The identification and verification processor 730 executes one or more computer programs under the control of the operating system.

Generally, the operating system and the circuit programs may be tangibly embodied in a computer-readable medium or carrier, e.g. one or more of the fixed or removable data storage devices 720, or other data storage or data communications devices. A quantizer 770 may be used for conversion of the analog signals to digital between the identification and verification processor 730 and any connecting digital device. Both operating system and the computer programs may be loaded from the data storage devices into the memory 740 of the identification and verification processor 730 for execution by the processor 710. Those skilled in the art will recognize that the memory 740 is optional, or may be a memory device embedded or otherwise couple to the identification and verification processor 730. Both the operating system and the generator programs comprise instructions which, when read and executed by the processor 710, cause the identification and verification processor 730 to perform the steps necessary to execute the steps or elements of the present invention. The resulting digital output 760 is produced.

Although one service request system configuration is illustrated in Fig. 7, those skilled in the art will recognize that any number of different configurations performing similar functions may be used in accordance with the present invention.

The above specification, examples and data provide a complete description of the manufacture and use of the composition of the invention. Since many embodiments of the invention may be made without departing from the spirit and scope of the invention, the invention resides in the claims hereinafter appended.

## WHAT IS CLAIMED

1. A portable method of real-time identification and verification of the identity of a person comprising the following steps:

providing a portable handheld device;  
capturing an image of a fingerprint;  
processing the fingerprint image to determine if the finger print image meets a predetermined quality level;  
storing fingerprint images that satisfy the predetermined fingerprint quality level in temporary data storage of the portable handheld device;  
transmitting fingerprint images that satisfy the predetermined fingerprint quality level to a central processor for processing;  
processing the transmitted fingerprint images to determine if there is matching fingerprint information in central data storage;  
receiving data from the central processor relating to the processed fingerprint image; and  
displaying the data received on a display of the portable handheld device.

2. The method of claim 1, wherein the step of capturing a fingerprint image includes the steps of:

positioning the finger on a finger receiving surface of the portable device; and  
scanning a slap imprint of the finger.

3. The method of claim 2, wherein the finger receiving surface captures fingerprint images in varying illumination conditions ranging from bright sunlight to total darkness.

4. The method of claim 1, wherein the step of capturing a fingerprint image includes the steps of:

positioning the finger on a finger receiving surface of the portable device; and  
scanning a rolled fingerprint.

5. The method of claim 1, wherein the step of capturing a fingerprint comprises scanning a latent imprint.

6. The method of claim 1, wherein the step of capturing a fingerprint image includes the step of determining the image quality of the fingerprint captured.

7. The method of claim 1, wherein the step of transmitting fingerprint images includes the steps of:

a wireless transmission from the portable handheld device to a wireless mobile unit for processing; and

wireless transmission from the wireless mobile unit to the central processor for comparison of the fingerprint images transmitted to a plurality of previously stored images to immediately determine identity and background information on individuals being fingerprinted in the field.

8. The method of claim 1, including the step of capturing a facial image and transmitting the captured facial image to a central processor, wherein the step of transmitting the facial image to the central processor includes the steps of:

a wireless transmission from the portable handheld device to a wireless mobile unit for processing; and

wireless transmission from the wireless mobile unit to the central processor for comparison of the facial images transmitted to a plurality of previously stored

facial images to immediately determine identity and background information on individuals in the field.

9. The method of claim 1 further including the steps of recording, displaying, and transmitting live video images captured, wherein the step of transmitting the live video images captured includes the steps of:

a wireless transmission of the live video images captured from the portable handheld device to a wireless mobile unit for processing; and

wireless transmission of the live video images captured from the wireless mobile unit to the central processor for storage in central data storage.

10. The method of claim 1 further including the steps of recording, playing back, displaying, analyzing, and transmitting audio information captured, wherein the step of transmitting the audio information captured includes the steps of:

a wireless transmission of the audio information captured from the portable handheld device to a wireless mobile unit for processing; and

wireless transmission of the audio information from the wireless mobile unit to the central processor for comparison of the audio information transmitted to a plurality of previously stored voice files to immediately determine identity and background information on individuals in the field.

11. The method of claim 1 further including the step of, capturing identification data from an external source.

12. The method of claim 11 wherein the external source is an identification card having an magnetic strip bar code.

13. The method of claim 11 wherein the external source is a smart card.

14. The method of claim 1 including the step of capturing geographical position and direction data.

15. The method of claim 1 including the step of transmitting a signal for emergency assistance.

16. A portable apparatus for identification and verification of a fingerprint comprising:

a housing having an ergonomic handle formed thereon that provides for one hand operation and command of all the functions of the apparatus;

a user interface, attached to the housing for data input, display and receipt, the user interface including at least a finger-receiving surface for receiving images of a fingerprint and buttons for data entry and command execution;

a sensor positioned within the housing and electrically connected to the user interface for capturing the fingerprint images from the finger-receiving surface;

a processor electrically connected to the sensor for processing the fingerprint images captured to determine if the fingerprint images captured meet a minimum fingerprint quality level; and

a transmitter, electrically connected to the processor for transmitting fingerprint images to a central processor for identification and verification.

17. The portable apparatus of claim 16, wherein the portable handheld device further includes a module operating within the processor that provides for the capture and enhancement of the fingerprint image prior to transmittal.

18. The portable apparatus of claim 16, wherein the portable handheld device further includes data storage electrically connected to the sensor for storing the fingerprint images captured that meet a minimum fingerprint quality level.

19. The portable apparatus of claim 16, including a removable baffle for preventing illumination sources to interfere with capturing the fingerprint on the finger-receiving surface.

20. The portable apparatus of claim 16 including a recorder that records and plays back audio and video information that is analyzed by the processor.

21. The portable apparatus of claim 16 wherein the user interface includes a card reader for entry of identification data from smart cards or cards having magnetic strips.

22. The portable apparatus of claim 16 wherein the user interface includes a bar code reader for entry of identification data.

23. The portable apparatus of claim 16 including a GPS receiving electrically connected to the processor to provide for the capture of geographical position and direction data.

24. The portable apparatus of claim 16 including a wireless transmitter electrically connected to a single switch and the processor for transmitting a signal for emergency assistance when the single switch is engaged.

25. The portable apparatus of claim 16 wherein the user interface includes a data entry device for entry of text or voice data.

26. The portable apparatus of claim 16 wherein the sensor may detect latent fingerprints, the portable apparatus including a latent fingerprint alignment guide.

27. The portable apparatus of claim 16 wherein the transmitter is a wireless transmitter.

### Abstract of the Invention

A portable device for the live scanning of fingerprint, facial and crime scene images and the wireless transmission of said images to a central host system for identity verification. The portable device has the ability to allow the user to operate the device with a single hand. It can scan and record live fingerprint slap or roll images (via optical, solid state, or video sensors). It also includes a baffle that assists with the mechanical alignment of the fingerprints on the fingerprint sensor receiving surface and prevents bright light sources from interfering with fingerprint scans. The portable device also can scan, display, and record latent fingerprint images. It also has other data receiving and transmission functions, such as displaying and recording facial and incident scene images in conditions ranging from well lit to total darkness, recording and playing back incident scene audio information for incident description and contacting voice recordings for identification. The portable apparatus can also scan, record, and interpret magnetic stripe, smart card, or bar code information from standard and non-standard cards. It also obtains, displays, and records geographical position for incident description, mapping, and directional instruction to the user. It further provides an emergency transmission for assistance and provides a short-range wireless link to a mobile unit or a *direct wireless* link to the central site. It also provides for entry by the user of text data for demographics or operator use through either keyboard or voice activation.




Figure 1. Component Block Diagram






Figure 2A Removable Light Baffle




Figure 2B







Figure 3: Ergonomic design for single hand operation

**Fixture; Magnetic Stripe Card Reader**

**Figure 5: Data flow for roll fingerprint capture**



**Figure 6: Wireless Links to the apparatus**

**Fig. 7**

MERCHANT &amp; GOULD P.C.

## United States Patent Application

## COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor I hereby declare that: my residence, post office address and citizenship are as stated below next to my name; that

I verily believe I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: PORTABLE APPARATUS FOR IDENTIFICATION VERIFICATION

The specification of which

- a. ☒ is attached hereto  
b. ☐ was filed on \_\_\_\_\_ as application serial no. \_\_\_\_\_ and was amended on \_\_\_\_\_ (if applicable) (in the case of a PCT-filed application) described and claimed in international no. \_\_\_\_\_ filed \_\_\_\_\_ and as amended on \_\_\_\_\_ (if any), which I have reviewed and for which I solicit a United States patent.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, § 1.56 (attached hereto).

Thereby claim foreign priority benefits under Title 35, United States Code, § 119/365 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on the basis of which priority is claimed:

- a. ☒ no such applications have been filed.  
b. ☐ such applications have been filed as follows:

FOREIGN APPLICATION(S), IF ANY, CLAIMING PRIORITY UNDER 35 USC § 119			
COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	DATE OF ISSUE (day, month, year)

ALL FOREIGN APPLICATION(S), IF ANY, FILED BEFORE THE PRIORITY APPLICATION(S)			
COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	DATE OF ISSUE (day, month, year)

I hereby claim the benefit under Title 35, United States Code, § 120/365 of any United States and PCT international application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. APPLICATION NUMBER	DATE OF FILING (day, month, year)	STATUS (patented, pending, abandoned)

I hereby claim the benefit under Title 35, United States Code § 119(e) of any United States provisional application(s) listed below:

U.S. PROVISIONAL APPLICATION NUMBER	DATE OF FILING (Day, Month, Year)
60/162,592	29 October 1999

I hereby appoint the following attorney(s) and/or patent agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith:

Albrecht, John W.	Reg. No. 40,481	Leon, Andrew J.	Reg. No. 46,869
Ali, M. Jeffer	Reg. No. 46,359	Leonard, Christopher J.	Reg. No. 41,940
Anderson, Gregg I.	Reg. No. 28,828	Liepa, Mara E.	Reg. No. 40,066
Batzli, Brian H.	Reg. No. 32,960	Lindquist, Timothy A.	Reg. No. 40,701
Beard, John L.	Reg. No. 27,612	Lycke, Lawrence E.	Reg. No. 38,540
Berns, John M.	Reg. No. 43,496	McAuley, Steven A.	Reg. No. 46,084
Black, Bruce E.	Reg. No. 41,622	McDonald, Daniel W.	Reg. No. 32,044
Branch, John W.	Reg. No. 41,633	McIntyre, Jr., William F.	Reg. No. 44,921
Bremer, Dennis C.	Reg. No. 40,528	Mitchem, M. Todd	Reg. No. 40,731
Bruess, Steven C.	Reg. No. 34,130	Mueller, Douglas P.	Reg. No. 30,300
Byrne, Linda M.	Reg. No. 32,404	Nichols, A. Shane	Reg. No. 43,836
Campbell, Keith	Reg. No. P-46,597	Pauly, Daniel M.	Reg. No. 40,123
Carlson, Alan G.	Reg. No. 25,959	Phillips, Bryan K.	Reg. No. P-46,990
Caspers, Philip P.	Reg. No. 33,227	Phillips, John B.	Reg. No. 37,206
Chiapetta, James R.	Reg. No. 39,634	Plunkett, Theodore	Reg. No. 37,209
Clifford, John A.	Reg. No. 30,247	Prendergast, Paul	Reg. No. 46,068
Coldren, Richard J.	Reg. No. 44,084	Pytel, Melissa J.	Reg. No. 41,512
Daignault, Ronald A.	Reg. No. 25,968	Qualey, Terry	Reg. No. 25,148
Daley, Dennis R.	Reg. No. 34,994	Reich, John C.	Reg. No. 37,703
Dalglish, Leslie E.	Reg. No. 40,579	Reiland, Earl D.	Reg. No. 25,767
Daulton, Julie R.	Reg. No. 36,414	Samuels, Lisa A.	Reg. No. 43,080
DeVries Smith, Katherine M.	Reg. No. 42,157	Schmaltz, David G.	Reg. No. 39,828
DiPietro, Mark J.	Reg. No. 28,707	Schuman, Mark D.	Reg. No. 31,197
Edell, Robert T.	Reg. No. 20,187	Schumann, Michael D.	Reg. No. 30,422
Epp Ryan, Sandra	Reg. No. 39,667	Scull, Timothy B.	Reg. No. 42,137
Glance, Robert J.	Reg. No. 40,620	Sebald, Gregory A.	Reg. No. 33,280
Goggin, Matthew J.	Reg. No. 44,125	Skoog, Mark T.	Reg. No. 40,178
Golla, Charles E.	Reg. No. 26,896	Spellman, Steven J.	Reg. No. 45,124
Gorman, Alan G.	Reg. No. 38,472	Stoll-DeBell, Kirstin L.	Reg. No. 43,164
Gould, John D.	Reg. No. 18,223	Sumner, John P.	Reg. No. 29,114
Gregson, Richard	Reg. No. 41,804	Swenson, Erik G.	Reg. No. 45,147
Gresens, John J.	Reg. No. 33,112	Tellekson, David K.	Reg. No. 32,314
Hamer, Samuel A.	Reg. No. 46,754	Trembath, Jon R.	Reg. No. 38,344
Hamre, Curtis B.	Reg. No. 29,165	Tuchman, Ido	Reg. No. 45,924
Harrison, Kevin C.	Reg. No. P-46,759	Underhill, Albert L.	Reg. No. 27,403
Hertzberg, Brett A.	Reg. No. 42,660	Vandenburgh, J. Derek	Reg. No. 32,179
Hillson, Randall A.	Reg. No. 31,838	Wahl, John R.	Reg. No. 33,044
Holzer, Jr., Richard J.	Reg. No. 42,668	Weaver, Karrie G.	Reg. No. 43,245
Johnston, Scott W.	Reg. No. 39,721	Welter, Paul A.	Reg. No. 20,890
Kadievitch, Natalie D.	Reg. No. 34,196	Whipps, Brian	Reg. No. 43,261
Karjeker, Shaukat	Reg. No. 34,049	Whitaker, John E.	Reg. No. 42,222
Kastelic, Joseph M.	Reg. No. 37,160	Wickhem, J. Scot	Reg. No. 41,376
Kettelberger, Denise	Reg. No. 33,924	Williams, Douglas J.	Reg. No. 27,054
Keys, Jeramie J.	Reg. No. 42,724	Withers, James D.	Reg. No. 40,376
Knearl, Homer L.	Reg. No. 21,197	Witt, Jonelle	Reg. No. 41,980
Kowalchyk, Alan W.	Reg. No. 31,535	Wu, Tong	Reg. No. 43,361
Kowalchyk, Katherine M.	Reg. No. 36,848	Xu, Min S.	Reg. No. 39,536
Lacy, Paul E.	Reg. No. 38,946	Zeuli, Anthony R.	Reg. No. 45,255
Larson, James A.	Reg. No. 40,443		

I hereby authorize them to act and rely on instructions from and communicate directly with the person/assignee/attorney/firm/ organization who/which first sends/sent this case to them and by whom/which I hereby declare that I have consented after full disclosure to be represented unless/until I instruct Merchant & Gould P.C. to the contrary.

Please direct all correspondence in this case to Merchant & Gould P.C. at the address indicated below:

Merchant & Gould P.C.  
P.O. Box 2903  
Minneapolis, MN 55402-0903



I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

2	<b>Full Name Of Inventor</b>	<b>Family Name</b> FISHER	<b>First Given Name</b> BARRY	<b>Second Given Name</b> ALLAN
0	<b>Residence &amp; Citizenship</b>	<b>City</b> MAPLE GROVE	<b>State or Foreign Country</b> MINNESOTA	<b>Country of Citizenship</b> USA
1	<b>Post Office Address</b>	<b>Post Office Address</b> 13961 92ND PLACE NORTH	<b>City</b> MAPLE GROVE	<b>State &amp; Zip Code/Country</b> MINNESOTA 55369/USA
<b>Signature of Inventor 201:</b>				<b>Date:</b>
2	<b>Full Name Of Inventor</b>	<b>Family Name</b> HENDRICKSON	<b>First Given Name</b> JACK	<b>Second Given Name</b> LEON
0	<b>Residence &amp; Citizenship</b>	<b>City</b> CARVER	<b>State or Foreign Country</b> MINNESOTA	<b>Country of Citizenship</b> USA
2	<b>Post Office Address</b>	<b>Post Office Address</b> 16985 COUNTY ROAD 40	<b>City</b> CARVER	<b>State &amp; Zip Code/Country</b> MINNESOTA 55315/USA
<b>Signature of Inventor 202:</b>				<b>Date:</b>
2	<b>Full Name Of Inventor</b>	<b>Family Name</b> GIESELMAN	<b>First Given Name</b> NEAL	<b>Second Given Name</b> JOSEPH
0	<b>Residence &amp; Citizenship</b>	<b>City</b> EAGAN	<b>State or Foreign Country</b> MINNESOTA	<b>Country of Citizenship</b> USA
3	<b>Post Office Address</b>	<b>Post Office Address</b> 1767 GABBRO TRAIL	<b>City</b> EAGAN	<b>State &amp; Zip Code/Country</b> MINNESOTA 55122/USA
<b>Signature of Inventor 203:</b>				<b>Date:</b>
2	<b>Full Name Of Inventor</b>	<b>Family Name</b> MISSLIN	<b>First Given Name</b> ANTHONY	<b>Second Given Name</b> RAY
0	<b>Residence &amp; Citizenship</b>	<b>City</b> CHANHASSEN	<b>State or Foreign Country</b> MINNESOTA	<b>Country of Citizenship</b> USA
4	<b>Post Office Address</b>	<b>Post Office Address</b> 8231 WEST LAKE COURT	<b>City</b> CHANHASSEN	<b>State &amp; Zip Code/Country</b> MINNESOTA 55317/USA
<b>Signature of Inventor 204:</b>				<b>Date:</b>
2	<b>Full Name Of Inventor</b>	<b>Family Name</b> GUZIK	<b>First Given Name</b> MICHAEL	<b>Second Given Name</b> RAYMOND
0	<b>Residence &amp; Citizenship</b>	<b>City</b> FRIDLEY	<b>State or Foreign Country</b> MINNESOTA	<b>Country of Citizenship</b> USA
5	<b>Post Office Address</b>	<b>Post Office Address</b> 1485 66TH AVENUE NORTHEAST	<b>City</b> FRIDLEY	<b>State &amp; Zip Code/Country</b> MINNESOTA 55432/USA
<b>Signature of Inventor 205:</b>				<b>Date:</b>

2	<b>Full Name Of Inventor</b>	<b>Family Name</b> KRUSE	<b>First Given Name</b> CURTIS	<b>Second Given Name</b> LEE
0	<b>Residence &amp; Citizenship</b>	<b>City</b> EAGAN	<b>State or Foreign Country</b> MINNESOTA	<b>Country of Citizenship</b> USA
6	<b>Post Office Address</b>	<b>Post Office Address</b> 1113 PARKVIEW LANE	<b>City</b> EAGAN	<b>State &amp; Zip Code/Country</b> MINNESOTA 55123/USA
<b>Signature of Inventor 206:</b>				<b>Date:</b>
2	<b>Full Name Of Inventor</b>	<b>Family Name</b> CAYO	<b>First Given Name</b> WILLIAM	<b>Second Given Name</b> RICHARD
0	<b>Residence &amp; Citizenship</b>	<b>City</b> PRIOR LAKE	<b>State or Foreign Country</b> MINNESOTA	<b>Country of Citizenship</b> USA
7	<b>Post Office Address</b>	<b>Post Office Address</b> 4887 BIANCA CIRCLE	<b>City</b> PRIOR LAKE	<b>State &amp; Zip Code/Country</b> MINNESOTA 55372/USA
<b>Signature of Inventor 207:</b>				<b>Date:</b>
2	<b>Full Name Of Inventor</b>	<b>Family Name</b> STOLTZMANN	<b>First Given Name</b> DAVID	<b>Second Given Name</b> EUGENE
0	<b>Residence &amp; Citizenship</b>	<b>City</b> BAYPORT	<b>State or Foreign Country</b> MINNESOTA	<b>Country of Citizenship</b> USA
8	<b>Post Office Address</b>	<b>Post Office Address</b> 368 NORTH 9TH STREET	<b>City</b> BAYPORT	<b>State &amp; Zip Code/Country</b> MINNESOTA 55003/USA
<b>Signature of Inventor 208:</b>				<b>Date:</b>
2	<b>Full Name Of Inventor</b>	<b>Family Name</b> JANCSEK	<b>First Given Name</b> JOHN	<b>Second Given Name</b> J.
0	<b>Residence &amp; Citizenship</b>	<b>City</b> BLAINE	<b>State or Foreign Country</b> MINNESOTA	<b>Country of Citizenship</b> USA
9	<b>Post Office Address</b>	<b>Post Office Address</b> 11849 MADISON STREET	<b>City</b> BLAINE	<b>State &amp; Zip Code/Country</b> MINNESOTA 55434/USA
<b>Signature of Inventor 209:</b>				<b>Date:</b>



## § 1.56 Duty to disclose information material to patentability.

(a) A patent by its very nature is affected with a public interest. The public interest is best served, and the most effective patent examination occurs when, at the time an application is being examined, the Office is aware of and evaluates the teachings of all information material to patentability. Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith in dealing with the Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section. The duty to disclose information exists with respect to each pending claim until the claim is canceled or withdrawn from consideration, or the application becomes abandoned. Information material to the patentability of a claim that is canceled or withdrawn from consideration need not be submitted if the information is not material to the patentability of any claim remaining under consideration in the application. There is no duty to submit information which is not material to the patentability of any existing claim. The duty to disclose all information known to be material to patentability is deemed to be satisfied if all information known to be material to patentability of any claim issued in a patent was cited by the Office or submitted to the Office in the manner prescribed by §§ 1.97(b)-(d) and 1.98. However, no patent will be granted on an application in connection with which fraud on the Office was practiced or attempted or the duty of disclosure was violated through bad faith or intentional misconduct. The Office encourages applicants to carefully examine:

(1) prior art cited in search reports of a foreign patent office in a counterpart application, and

(2) the closest information over which individuals associated with the filing or prosecution of a patent application believe any pending claim patentably defines, to make sure that any material information contained therein is disclosed to the Office.

(b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and

(1) It establishes, by itself or in combination with other information, a prima facie case of unpatentability of a claim;

(2) It refutes, or is inconsistent with, a position the applicant takes in:

(i) Opposing an argument of unpatentability relied on by the Office, or

(ii) Asserting an argument of patentability.

A prima facie case of unpatentability is established when the information compels a conclusion that a claim is unpatentable under the preponderance of evidence, burden-of-proof standard, giving each term in the claim its broadest reasonable construction consistent with the specification, and before any consideration is given to evidence which may be submitted in an attempt to establish a contrary conclusion of patentability.

(c) Individuals associated with the filing or prosecution of a patent application within the meaning of this section are:

(1) Each inventor named in the application:

(2) Each attorney or agent who prepares or prosecutes the application; and

(3) Every other person who is substantively involved in the preparation or prosecution of the application and who is associated with the inventor, with the assignee or with anyone to whom there is an obligation to assign the application.

(d) Individuals other than the attorney, agent or inventor may comply with this section by disclosing information to the attorney, agent, or inventor.